

XGA SERIES

Clean, Reliable Power in a durable enclosure. If you demand professional amplification performance, the XGA Series is perfect for delivering pure, consistent wattage night after night, year in and year out! Brings watts of Instant Peak Power making it ideal for PA systems and DJ rigs. We've designed this with our patented front to rear airflow technology powered by a variable speed thermal stabilizer to guarantee seamless, reliable performance every single night! Our XGA Series offers clean, dependable power in a lightweight body at an unmatched value.



XGA-5000

- 5,000 Watt IPP* High Power output to drive professional loudspeakers without clipping
- Front-to-rear airflow and cooling fan for thermal stability and reliability
- XLR and ¼" (6.5mm Jack) balanced
- Limiter circuit switch for amp output protection
- Stereo and Mono Bridge
- Variable speed fan for low noise
- Comprehensive front panel indicators including signal, clip, protect and bridge
- 3 Speakon outputs for Channels A/B/ Bridge
- 5-way binding banana plug channel outputs
- Bridge control switch

XGA-4000

- 4,000 Watt IPP* High Power output to drive professional loudspeakers without clipping
- Front-to-rear airflow and cooling fan for thermal stability and reliability
- XLR and ¼" (6.5mm Jack) balanced
- Limiter circuit switch for amp output protection
- Stereo and Mono Bridge
- Variable speed fan for low noise
- Comprehensive front panel indicators including signal, clip, protect and bridge
- 3 Speakon outputs for Channels A/B/ Bridge
- 5-way binding banana plug channel outputs
- Bridge control switch

XGA-3000

- 3,000 Watt IPP* High Power output to drive professional loudspeakers without clipping
- Front-to-rear airflow and cooling fan for thermal stability and reliability
- XLR and ¼" (6.5mm Jack) balanced
- Limiter circuit switch for amp output protection
- Stereo and Mono Bridge
- Variable speed fan for low noise
- Comprehensive front panel indicators including signal, clip, protect and bridge
- 3 Speakon outputs for Channels A/B/ Bridge
- 5-way binding banana plug channel outputs
- Bridge control switch

XGA-2000

- 2,000 Watt IPP* High Power output to drive professional loudspeakers without clipping
- Front-to-rear airflow and cooling fan for thermal stability and reliability
- XLR and ¼" (6.5mm Jack) balanced
- Limiter circuit switch for amp output protection
- Stereo and Mono Bridge
- Variable speed fan for low noise
- Comprehensive front panel indicators including signal, clip, protect and bridge
- 3 Speakon outputs for Channels A/B/ Bridge
- 5-way binding banana plug channel outputs
- Bridge control switch